TRENDSETTER 800 III SPECIFICATIONS

Product description

The Kodak® Trendsetter® 800 III is a semiautomatic platesetter that uses Kodak thermal imaging technology to expose plates for conventional and waterless printing. The Trendsetter 800 III device can be equipped with an Autoloader or ContinuousLoad option and can be upgraded to Quantum.

Features and benefits

- Kodak thermal imaging head—2400 dpi
- Multiple imaging speed options available
- Dynamic autofocus
- Semiautomatic media loading and unloading
- Automatic registration
- Automatic plate clamping

Prerequisites

- Compliance with *Trendsetter 400/800 III Site Preparation Guide* (707-00566)
- Kodak-approved workstation (contact a sales representative for workstation options)
- Kodak Prinergy®, Kodak Prinergy® Evo™ workflow system, or approved third-party workflow capable of supplying 1-bit TIFF files
- Processing line and other system peripherals must be of adequate performance in order to achieve full throughput. Consult with appropriate vendors to ensure sufficient performance can be achieved.

Components

Standard hardware:

- Plot engine
- Kodak thermal imaging head—40 W, 2400 dpi (—50 W, 2400 dpi for X-speed imaging)
- Standard S-speed imaging
- Debris removal system
- Semiautomatic media loader

Documentation:

- *Trendsetter 400/800 III Visual Reference Guide* (653-01284)
- *Trendsetter Output Devices Safety Guide* (761-00029)

Training included: On-site operator training for one person

Consumables included: Filters

Options

Optional hardware:

- F-speed imaging
- V-speed imaging
- X-speed imaging
- Autoloader (see *Autoloader Specifications* (707-00564) for details)
- ContinuousLoad (see *ContinuousLoad Specifications* (707-00565) for details)

Optional software:

- Kodak Staccato® 25 Series Screen sets available as an option with Prinergy and Prinergy Evo workflows

Input

Media size (maximum/ minimum)	• Around-drum circumference: 838 mm (33 in.) maximum, 270 mm (10.6 in.) minimum • Along-drum axis: 1143 mm (45 in.) maximum, 215 mm (8.5 in.) minimum
Media type	• Thermal IR-sensitive aluminum plate and film, 830 nm • For a list of qualified media, see the individual media specifications .
Media thickness	0.14 mm to 0.40 mm (0.0055 in. to 0.016 in.) for plates[1]

Output

Non-imaged areas	6.1 mm (0.24 in.) along leading edge and 7.6 mm (0.30 in.) along trailing edge
Resolution	• 2400 dpi or 1200 dpi • Maximum recommended line screen: 200 lpi • Staccato screen sets[2]: Staccato 25 Series option available

Specific functions

Automatic registration:	• Media edge—registered horizontally to pins mounted on drum • Vertical edge located with precise optical sensing
Automatic clamping	Adjusts to any plate size (within the maximum and minimum allowed)

Performance

Imaging speed	• S-speed (standard): 330 mm (13.0 in.) per minute @ 2400 dpi • F-speed (option): 536 mm (21.1 in.) per minute @ 2400 dpi • V-speed (option): 850 mm (33.5 in.) per minute @ 2400 dpi • X-speed (option): 944 mm (37.2 in.) per minute @ 2400 dpi
Throughput[3]	• S-speed: 15 plates per hour (16 with Autoloader or ContinuousLoad option) • F-speed: 22 plates per hour (24 with Autoloader or ContinuousLoad option) • V-speed: 30 plates per hour (34 with Autoloader or ContinuousLoad option) • X-speed: 37 plates per hour (42 with Autoloader option, 40 with ContinuousLoad option)
Repeatability[4]	± 5 microns (± 0.2 mil) between two consecutive exposures on the same plate left on the drum (at largest plate size and at constant temperature)

1. Limited to 0.20 mm to 0.30 mm (0.008 in. to 0.012 in.) for X-speed imaging
2. Support for Staccato is limited to qualified plates; consult your Kodak representative for the current qualification list.
3. Imaging time is based on a 1030-mm (40.5-in.) plate with a media sensitivity of 120 mJ per cm^2. Imaging time is dependent on media sensitivity.
4. Specifications for metallic media only

Registration[4]	± 25 microns (± 1.0 mil) between image and plate edge (at largest plate size and at constant temperature)
Environmental conditions	• 17º to 30ºC (63º to 86ºF) and 20% to 70% relative humidity, non-condensing • Prepress or platemaking environment • Some media may restrict the operating range of the platesetter system. Consult the media manufacturer for their recommended temperature and humidity ranges for plate operations and storage.
Electrical requirements	• Rating: 200–240 VAC, 15 A, 50/60 Hz, (dedicated single-phase branch circuit required, 20 A for NA and 16 A for EU) • Actual current draw while imaging: 3.4 A, 0.790 kW
Noise emissions	The Trendsetter output device has been designed, tested, and evaluated for compliance with the maximum noise emission limit permitted for a light industrial environment—80 dB(A). Noise emissions from the Trendsetter output device will not exceed 74 dB(A) when tested in accordance with EN ISO 7779:2001, Acoustics - Measurement of airborne noise emitted by information technology and telecommunications equipment.
Compressed air requirements	370 liters per minute at 620-830 kPa (13 scfm @ 90-120 psig)
Equipment dimensions	• Width 2830 mm (111.4 in.) • Depth 1070 mm (42 in.) • Height 1600 mm (63 in.)
Equipment weight	• Trendsetter platesetter 544 kg (1200 lb.) • Debris removal system (UDRC) 57 kg (125 lb.)
Regulatory compliance	• ELECTRICAL/MECHANICAL: CSA 60950-1, UL 60950-1, EN 60950-1, EN 60204-1, Low Voltage Directive 73/23/EEC, Directive of Machinery 98/37/EC • LASER SAFETY: CDRH 21 CFR 1040.10, EN 60825-1 (Class 1 Laser Product) • EMC: FCC Part 15, (Class A), EN 55022/CISPR-22 (Class A), EN 55024, EN 61000-3-3, Directive of Electromagnetic Compatibility 2004/108/EC