

Matchprint Virtual

for InSite Prepress Portal

Version 5.0

Customer Quick Start Guide

English

731-00698C-EN Rev C

Copyright



© 2006 Kodak. All rights reserved.

Kodak, Creo, InSite, and Matchprint are trademarks of Kodak.

Adobe, Acrobat, Adobe Illustrator, Distiller, Photoshop, PostScript, and PageMaker are trademarks of Adobe Systems Incorporated.

Apple, iMac, Power Macintosh, Mac OS, AppleShare, AppleTalk, TrueType, ImageWriter, and LaserWriter are registered trademarks of Apple Computer, Inc. Macintosh is a trademark of Apple Computer, Inc., registered in the U.S.A. and other countries.

PANTONE, Hexachrome, PANTONE Hexachrome, and PANTONE MATCHING SYSTEM are the property of Pantone, Inc.

PEARL, PEARLsetter, PEARLhdp, PEARLdry, and PEARLgold are registered trademarks of Presstek, Inc.

XEROX® is a trademark of XEROX CORPORATION.

http://graphics.kodak.com/

731-00698C-EN Rev C

Revised December 2007

Contents

What Is Matchprint Virtual? 1
Software/Hardware Requirements 1
Installing Matchprint Virtual Calibration Software 1
Setting System Preferences 2
Calibrating Color Monitors 3
Setting Monitor Luminance Levels 4
Assigning Color Roles 5
Reviewing and Approving Color-Managed Pages in Smart Review 6
Removing Matchprint Virtual Calibration Software 7

What Is Matchprint Virtual?

Kodak® Matchprint® Virtual software allows users who run Apple® Mac OS® X systems with an approved, calibrated color monitor to perform color-accurate proofing in the Kodak InSite™ Smart Review software. This document explains how to install the Matchprint Virtual software, set color targets, adjust monitor settings, and configure the InSite Prepress Portal for soft color proofing.

The steps are:

- Install Matchprint Virtual monitor calibration software on your Apple® Macintosh® computer, and connect the calibrator—see page 1.
- Set system preferences—see page 2.
- Calibrate the color monitor—see page 3.
- Set monitor luminance levels—see page 4.
  - ❒ Ensure that you have color user rights—see page 5
  - ❒ Review, annotate, and approve color-managed pages in Smart Review—see page 6.

Software/Hardware Requirements

You must use an approved and calibrated Macintosh system to ensure color-accurate viewing. For the latest hardware and software requirements, see the *Matchprint Virtual 5.0 Release Notes*, available under **Product Documentation** at http://graphics.kodak.com/matchprintvirtual/.

Installing Matchprint Virtual Calibration Software

Before you view color-accurate pages, you need to be sure that your monitor can consistently display a standard quality of color. Use only a qualified EIZO ColorEdge® or Apple Cinema Display™ color calibration monitor—for a list of qualified monitors, see the *Matchprint Virtual 5.0 Release Notes,* available under **Product Documentation** at http://graphics.kodak.com/matchprintvirtual/.

Matchprint Virtual calibration software runs the monitor through a sequence of color patches, measures each color, compares it to predefined color settings, and records the results.

Install the latest version of Matchprint Virtual calibration software on each Macintosh computer that will be used to perform monitor proofing.

If you have version 3.2 of Matchprint Virtual calibration software installed, you must remove it first—see *Removing Matchprint Virtual Calibration Software* on page 7.

To install the latest Matchprint Virtual calibration software:

1. Log on to the Macintosh computer as an Administrator.
2. Open a Web browser and locate the Matchprint Virtual Web site at http://graphics.kodak.com/matchprintvirtual
3. Download the Matchprint Virtual software and all updates to your Macintosh desktop.
4. Double-click the installer icon and follow the prompts to complete installation of the software.
5. Restart your computer.
6. Double-click any updater icon and follow the prompts to complete installation of the updates.
7. Restart your computer.
8. Connect the calibrator to the USB port on the computer or monitor, or to a self-powered USB hub.

   Important: Do not use the USB port located on the keyboard.

To use the calibration software, see *Calibrating Color Monitors* on page 3.

Setting System Preferences

If your computer system is running the Energy Saver feature, or your screen saver is set to start frequently, you need to adjust the settings so that they do not interfere with monitor calibration.

Configuring the Energy Saver

The Energy Saver feature puts your computer and your monitor into sleep mode whenever they are inactive for a defined period of time. It can also be set to start your computer automatically each working day.

If the Energy Saver shuts down your monitor and it stays off for more than five minutes, you must wait an hour for it to warm up before you can calibrate. To avoid the wait, ensure that the sleep mode is disabled. You may also want to set the Energy Saver to start the computer each working day at least an hour before you expect to calibrate.

To configure the Energy Saver:

1. From the **Apple** menu, select **System Preferences**.
2. Click **Energy Saver**.
3. If the lock at the bottom of the Energy Saver window is closed, it must be unlocked before changes can be made. Click the lock and enter the administrator username and password to unlock it.
4. Under **Put the computer to sleep when it is inactive for:**, set the sliding scale to **Never**.

5. Under **Put the display to sleep when the computer is inactive for:**, set the sliding scale to **Never**.

   Important: Matchprint Virtual software will not calibrate a monitor if it detects an Energy Saver setting other than Never.

6. Ensure that the check box beside **Put the hard disk(s) to sleep if possible** is cleared.
7. Click **Schedule**.
8. Select the check box beside **Start up or wake**.
9. From the menu, select a day or days. Beside **at**, type a time of day.
10. Click **OK**.
11. Click the lock to prevent anyone else from changing the settings.
12. Close the Energy Saver window.

Configuring Screen Savers

You must prevent your screen saver from launching during calibration and interfering with measurement.

To configure a screen saver:

1. From the **Apple** menu, select **System Preferences**.
2. Click **Desktop & Screen Saver**.
3. Click the **Screen Saver** tab.
4. Select a screen saver.
5. Under **Start screen saver**, set the sliding scale to at least 1 hour 30 minutes.
6. Close the Desktop & Screen Saver window.

Calibrating Color Monitors

After you have installed the Matchprint Virtual calibration software, you must calibrate your monitors every 24 hours to ensure accurate color viewing.

Note: Monitors must be turned on for at least one hour before they can be calibrated.

1. At the Dock, click and hold the **Matchprint Virtual** icon. 
2. Select **MVP Calibrate System**.
3. Follow the prompts to calibrate the monitors.

During calibration, your Matchprint Virtual calibration software checks the deltaE and white point luminance of your monitor. If the deltaE exceeds 2.5, or if the display cannot achieve the luminance value that is set in the software, calibration fails.

Monitor Calibration Reminder

When calibration expires, a reminder appears. You can select **Dismiss for 24 hours**, or **Calibrate**.

The reminder may also appear when the ambient room temperature increases or decreases by 5°C or more, or when the calibrator is left on the monitor.

For more information about calibrating color monitors, see the *Matchprint Virtual Monitor Calibration Quick Reference Card*, available under **Product Documentation** at http://graphics.kodak.com/matchprintvirtual/.

Setting Monitor Luminance Levels

The first time you calibrate the monitor, check its maximum luminance setting and change it to a lower, fixed luminance value to increase the viewing lifetime.

In a dual-monitor system, it is also important that the luminance of the two monitors matches so that color perception is not affected.

To check the maximum luminance settings of a new monitor:

1. At the Dock, click and hold the **Matchprint Virtual** icon. .
2. Select **MVP Preferences**.
3. Click the **Settings** tab, select a monitor, and click **Show Settings**.

   Tip: You can also double-click the monitor name to open its **Preferences** dialog box.
4. Ensure that **Maximum Luminance Method** is selected.
5. Click **Save**.
6. If you are calibrating a dual-monitor systems, repeat Steps 1 to 5 for the second monitor.
7. Calibrate the monitor—see *Calibrating Color Monitors* on page 3.

   When calibration is complete, the following message appears:

   ```
   Calibrate System on this monitor passed
   Color Verification:
   Luminance:
   ```
8. Record the color verification and luminance values.

To change to a fixed luminance setting:

1. At the Dock, click and hold the **Matchprint Virtual** icon. .
2. Select **MVP Preferences**.
3. Click the **Settings** tab, select the monitor, and click **Show Settings**.

   Tip: You can also double-click the monitor name to open its **Settings** dialog box.

   a. Select **Fixed Luminance Method**.

   b. Type a value that is 10% less than the lower of the two luminance values you recorded when you calibrated the monitors.

      Example (calibrating a single monitor):

      Your monitor has a luminance value of 255. Type `230` (255 - 25). This is the luminance value that the monitor must achieve for calibration to succeed.

Example (calibrating a dual-monitor system):

Your first monitor has a luminance value of 280 and your second monitor has a luminance value of 255. Since 255 is the lower value, type 230 (255 - 25). This is the luminance level that both monitors must achieve for calibration to succeed.

4. Click **Save**.
5. Wait 15 minutes and recalibrate the monitor.
6. If you are calibrating a dual-monitor system, repeat Steps 1 to 5 for the second monitor.

Troubleshooting: The monitor fails to calibrate.

As monitors age, they may fail to calibrate because they cannot achieve the fixed luminance level or the required deltaE (2.5 or less). When this happens:

1. Change back to the maximum luminance method.
2. Wait 15 minutes and recalibrate the monitor.
3. Record the maximum level that each monitor can achieve.
4. Change to the fixed luminance method and set a value that is 10% less than the lowest maximum luminance value you recorded.
5. Wait 15 minutes and recalibrate the monitor.

Assigning Color Roles

Prepress Portal users who view color-accurate pages in Smart Review must have a role that includes Color Management rights and Annotate rights.

To assign a Color role to users:

1. Log on to Prepress Portal.

   Note: You must have a Customer role that includes the Modify Customer right.
2. Click **Customers**.
3. Locate the customer name and click the row to expand the options. Click **Administration**.
4. In the **User/Group Name** column, click the name of the user that needs to work on color-managed pages.
5. In the **User Roles** area, select the Color role from the **Default Job Role** list.

   Note: The name of the Color role may vary, depending on the requirements of your workflow. The role must contain the View Color Management, Edit Color Management, and Approval rights. For assistance in selecting the correct role, contact your system administrator.
6. Click **Update**.
7. Click **X** to log out of Prepress Portal.

For more information, see the Prepress Portal Help.

Reviewing and Approving Color-Managed Pages in Smart Review

Before using Smart Review to review and approve color-managed pages, check the following:

- The Mac OS operating system must recognize the files as safe for downloading. To check this:
  a. Start the Safari browser.
  b. From the **Safari** menu, select **Preferences**.
  c. On the **General** tab, ensure that **Open "safe" files after downloading** is selected.
- You must have Color Management rights in the Prepress Portal software in order to see the options for color proofing. For information, see *Assigning Color Roles* on page 5.

To review and approve color-managed pages in Smart Review:

1. Log on to Prepress Portal.
2. On the **Summary** tab for the job, click **Smart Review**.
3. Click the page you want to view in the panel on the left.
4. Click **Full Screen Preview**.

   The Smart Review toolbars disappear. The color-managed page appears in actual size (1 inch on the monitor = 1 inch on the page
5. Review the page for color quality.

   If an arrow displays along one or more of the page borders, the page does not fit on the monitor. Move the mouse towards the arrow to scroll the image across the monitor.
6. Move the mouse. A **Close** button appears in the bottom right corner. Click it to return to Smart Review.
7. Annotate the page, if necessary
8. Approve the page, reject the page, or request corrections.

Important: If the page has been set to require color approval but you have not calibrated your monitor within the past 24 hours, you will be unable to approve the page for color.

For more information about reviewing and approving color-managed pages in Prepress Portal, see the Color Approval In Smart Review Quick Reference Card, available under **Product Documentation** at http://graphics.kodak.com/matchprintvirtual/.

Removing Matchprint Virtual Calibration Software

This section describes how to remove Matchprint Virtual calibration software.

Note: You do not need to remove Matchprint Virtual calibration software before you upgrade to a later version, as long as you are replacing version 4.0 or later.

To uninstall Matchprint Virtual calibration software, version 3.x:

1. Log on to the Macintosh computer as an Administrator.
2. Delete the **MATCHPRINT Virtual** icon from the Dock.
3. Insert the Matchprint Virtual calibration software CD, version 3.x, into the CD drive.
4. Double-click the **MVP-LCD v3.x.x Installer** icon on your desktop.
5. Double-click the **MVP LCD v.3.x.x Installer** icon.
6. Type your Administrator password.
7. In the License dialog box, click **Accept**.
8. In the Installer dialog box, select **Uninstall** from the menu and click **Uninstall**.
9. Click **Continue**.

   The Matchprint Virtual calibration software is removed. A confirmation message appears.
10. Click **OK** and **Quit**.

To remove Matchprint Virtual calibration software, version 4.0 or later:

1. Log on to the Macintosh computer as an Administrator.
2. Open your Apple Safari™ browser software and type `http://graphics.kodak.com/matchprintvirtual/`
3. Under **MATCHPRINT Virtual Monitor Calibration Software**, click **Download now.**
4. Under **Uninstallers**, click the version of Matchprint Virtual calibration software that you want to remove and download it to your desktop.
5. Double-click the Uninstaller icon on your desktop.
6. Type your Administrator username and password.

   The Matchprint Virtual calibration software is removed. A confirmation message appears.
7. Click **OK**.