Kodak Graphic Communications Canada Company
3700 Gilmore Way
Burnaby, B.C., Canada
V5G 4M1
Tel: 1.604.451.2700
Fax: 1.604.437.9891

Request support:
ecentral.creo.com
http://graphics.kodak.com

Internal:
Release date: 15 November, 2007

Product bulletin

Trendsetter VLF Power and Air Consumption

Trendsetter VLF

Electrical: Rated 200-240 V AC (+6%/-10%) single phase, 50/60 Hz, 16 A

Maximum load conditions: 5 A, 1 kW imaging

Idle: 4 A, 800 W

Pneumatic: Rated maximum 120 psi / 8 bar and minimum 90 psi / 6.2 bar.

Peak consumption[1]: 283 SL / min @ 690 kPa (10 SCFM @ 100 psi)

Trendsetter VLF Autoloader

Trendsetter VLF including the Multi-Cassette Unit or Single Cassette Unit.

Electrical: Rated 200-240 V AC (+6%/-10%) single phase, 50/60 Hz, 16 A

Maximum load conditions: 5 A, 1 kW imaging, 10.5 A, 1600 W MCU cycle

Idle: 4 A, 800 W

Pneumatic: Rated maximum 120 psi / 8 bar and minimum 90 psi / 6.2 bar.

Peak consumption[1]: 800 SL/min @ 690 kPa (28.3 SCFM @ 100 psi)

About Kodak Graphic Communications Group (GCG)

The leading provider of graphic communications solutions worldwide, Kodak's Graphic Communications Group (GCG) offers image capture systems; professional color, copydot, and high-speed document scanning systems; inkjet printing and proofing systems; workflow and color management software; thermal imaging devices for film, plates, and proofs; high-quality proofing media, printing plates, and recording film; on-demand color and black-and-white printing systems; data storage products; and professional services. With corporate headquarters located in Rochester, N.Y., Kodak (NYSE: EK) has the largest global sales force and is committed to a digitally oriented growth strategy. For more information, visit www.graphics.kodak.com.

© Kodak, 2007. Kodak and XXX are trademarks of Kodak.

[1] Peak consumption is listed, where the average is considerably less but dependent upon quantity of plates imaged per hour.