TIFF FRONTEND LITE SPECIFICATIONS

Product Description

The TIFF FrontEnd Lite Workstation is an OptiPlex GX270 1-CPU workstation.

Base Configuration

Model
- DELL OptiPlex GX270 Mini-Tower workstation based on Intel Hyper-threading Pentium IV Xeon Processor
  - The workstation has 4 memory DIMM slots; for a maximum of 2 GB MB Non-ECC 400MHz DDR SDRAM

CPU
- 1 x 3060 MHz (3.06GHz), Intel Hyper-threading Pentium IV Xeon Processor (800 MHz front side bus, 512 KB Cache)

Memory
- 1 GB (2 x 512MB DIMMs) of Non-ECC DDR SDRAM

System Disk
- 1 x 80 GB Enhanced IDE S.M.A.R.T. II Ultra ATA/66 7,200 RPM disk drive

Data Disk
- 1 x 80 GB Enhanced IDE S.M.A.R.T. II Ultra ATA/66 7,200 RPM disk drive

Controller
- None

Accessories
- 1 x EIDE DVD-CD ROM drive
- 1 x 1.44 MB floppy drive
- 1 x Integrated Intel 10/100/1000 Copper Gigabit NIC controller
- 1 x Integrated Intel DVMT Video controller
- 19" color monitor
- 1 x Keyboard
- 1 x PS/2 Mouse
- 1 serial port

Power Supply
- Standard 200W Power Supply

Operating System
- Windows 2000 Professional

Documentation
- DELL OptiPlex GX270 Workstation User Manual
- Windows 2000 User Manual

Vendor Specification
http://configure.us.dell.com/dellstore/config.aspx?c=us&cs=04&kc=6W463&l=en&oc=GX270T

Options

CPU	• None
Memory	• Expandable up to 2 GB (totaling 4 x 512MB DIMMs)
Internal Storage	• None
External Storage	• N/A
Removable Storage	• N/A
Controller	• N/A
UPS	• APC SmartUPS with UPS control software included
Network	• See Prinergy Network Specifications (Creo P/N: 72-3303x)