Kodak®
3700 Gilmore Way
Burnaby, B.C., Canada
V5G 4M1
Tel: 1.604.451.2700
Fax: 1.604.437.9891

Request support:
ecentral.creo.com

graphics.kodak.com

Internal: 707-00548A-EN-A
Release date: Jan 30, 2007

Product Specification

Dell OPTI745 Product Spec

Product Description

The Performance Workflow Workstation Opti745 is a High Performance Workstation with Single Core2Duo Processor, SATA Drives, and DDR2 Memory.

Feature Overview

- 1x Intel Core2Duo CPU
- 1x Integrated Gigabit NIC
- 2x 80GB Internal SATA Non-Hot Swap Disks
- 2GB DDR2 Memory
- 2x PCI 3.3v slots, 2x PCI-Express slots
- 8x USB 2.0 ports (2 on the front)
- 4x DDR2 Memory slots
- One Integrated Video.

Components

Standard Hardware

CPU	1x 1.86Ghz Intel E6300 Core2Duo Processor, 1066MHz FSB, 2MB L2 Cache
Chipset	Intel® Q965 Express with ICH8
Memory	2GB base configuration. 2 slots (1 bank) available for expansion 667MHz DDR2 DIMMs, Rank2, 2 banks total, 2 DIMMs per Bank
Disks	2x 80GB Internal SATA II non-hotswap disks, 7.2Krpm.
Network Interface	Broadcom 10/100/1000BaseT NIC (5754)
Power Supply	1x 305 Watt Manual Select Power Supply
Video	Intel® Integrated GMA 3000
I/O Ports	1x Serial Port 8x USB 2.0 Ports (6 in back, 2 in front)
PCI Slots	2x PCI 33Mhz, 3.3v, 32bit, non-hot plug 1x PCI-express (16x slot, graphics adapter only) 1x PCI-express (1x slot)
CD/DVD	1 x DVD-ROM SATA Drive
Floppy	1 x 1.44 MB Floppy Drive

Accessories

Monitor	1 x 17" LCD monitor
Keyboard	Standard Windows USB Keyboard
Mouse	Optical USB 2-button Mouse with Scroll
Modem	1 x 56kbps USR External Modem (in North America only)
Software	Windows XP Pro CD (downgrade license to Windows 2000 Pro)

Options

For all Options check the Price Book for Part Numbers.

Additonal Serial Ports	Digi Acceleport 2x Port Serial controller is included when connecting to a Kodak Output Device. Controller occupies 1x PCI slot.
SCSI	• Adaptec 39U160 LVD SCSI Controller (MCE connectivity) • Adaptec 39U320 LVD SCSI Controller (Library connectivity) • LSI 8751D HVD SCSI Controller (MPE connectivity)
Memory	Non ECC 667MHz DDR2 SDRAM. 2 Banks total of 2 slots per bank • 2GB of 2x 1024MB DIMMs.
Network Adapters	Intel Pro1000 NICs are available for GMCE connectivity. Either the PCI-X or PCI-E adapters are available.

Environmental Conditions

Power (max load)	200VA
Heat Dissipation	700 BTU/hr fully configured
Temperature Range (Operating)	10º C to 35º C (50º F to 95º F)
Relative Humidity (Operating)	20% to 80% (non-condensing)

Equipment Physical Specs

Height	17.28” (43.9cm)
Width	7.8” (19.8cm)
Depth	19.7” (50.0cm) with bezel
Weight	19.1 Kg, 42 lb. (fully loaded)

About Kodak Graphic Communications Group (GCG)

The leading provider of graphic communications solutions worldwide, Kodak's Graphic Communications Group (GCG) offers image capture systems; professional color, copydot, and high-speed document scanning systems; inkjet printing and proofing systems; workflow and color management software; thermal imaging devices for film, plates, and proofs; high-quality proofing media, printing plates, and recording film; on-demand color and black-and-white printing systems; data storage products; and professional services. Creo joined the GCG in June 2005, when it became a wholly owned subsidiary of Kodak. With corporate headquarters located in Rochester, N.Y., Kodak (NYSE: EK) had sales of $13.5 billion in 2004 and is committed to a digitally oriented growth strategy.

© 2007 Kodak. The Creo product names mentioned in this document are trademarks or service marks of Creo Inc., a subsidiary of Kodak, and may be registered in certain jurisdictions. Other company and brand, product, and service names are for identification purposes only and may be trademarks or registered trademarks of their respective holders. Data subject to change without notice.